

LG CHEMICAL LTD

20 YOIDO-DONG, YONGDUNGPO-GU, SEOUL 150-721 KR

LUPOY GN-2101F (f1), LUPOY GN-2101F(m) (f1)**Polycarbonate (PC), furnished as pellets**

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.5	V-0	3	0	120	90	105
	3.0	V-0, 5VA	2	0	120	90	105

Comparative Tracking Index (CTI): 3

High-Voltage Arc Tracking Rate (HVTR): 3

Dielectric Strength (kV/mm): -

Dimensional Stability (%): -

High Volt, Low Current Arc Resis (D495): 7

Volume Resistivity (10^X ohm-cm): -**(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.****(m) - May be followed by 1 or 2 suffix letters from A-Z incl., except F, FF, FH.**

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.