





Switch disconnecter for solar application according to IEC 60947-3 by KEMA to be certified



Terminals Scheme							
Layer No.	Front Side		Symbol	Rear Side		On Positions	
	Left	Right		Left	Right	1	2 3 4
9	-2			-2		X	X
8		-2			-2	X	X
7	+2			+2		X	X
6		+2			+2	X	X
5	-1			-1		X	X
4		-1			-1	X	X
3	+1			+1		X	X
2		+1			+1	X	X
1			empty			X	X

Contacts are made in "X" marked position.
Symbols for interconnection: [

Technical data	Symbol	Merit	Unit
rated operational voltage (DC poles)	Ue	800	V dc
rated operational current (DC poles)	Ie	36	A dc
rated operational voltage (second rating DC poles, if requested)	Ue	600	V dc
rated operational current (second rating DC poles, if requested)	Ie	50	A dc
method of mounting	both bottom and single hole mounting [D]		
number of DC poles		4	
utilization category DC actuator	DC-21B	ordered without a knob	
positions	OFF at 3 hr, ON at 6 hr, OFF at 9 hr, ON at 12 hr		
rated impulse withstand voltage	Uimp	8	kV
insulation voltage	Ui	1000	V
rated thermal current uninterrupted duty	Iu	50	A
rated short-time withstand current (1s)	Icw	750	A
rated short-circuit making capacity	Icm	1,4	kA
rated conditional short-circuit current		5	kA
max power dissipation		28	W
method of operation	independent manual operation		
minimum required dimensions of enclosures L x W x H*		124 x 47 x 126,5	mm
* see the drawing for the height of the switch. The number of layers N is:		9	
Shaft length			mm
Enclosure depth from inside bottom to outside top, required for the switch and knob		159,5	mm
tightening torque terminal screws M4 , min. - max.	1,5	1,7	Nm
tightening torque panel mounting nut, min. - max.	2,0	2,5	Nm
tightening torque M3 screw in the standard black knob, min. - max.	0,5	0,7	Nm
minimum required fine wire cross-section: IEC60947-1, table 9		2x6	mm ²
ambient temperature allowed between		- 20 to + 70 °C	°C
storage temperature allowed between		- 40 to + 80 °C	°C
maximum relative humidity, without condensation at 20 °C		90	%
pollution degree		2	
IP rating terminals		IP20	
IP rating gland of the shaft in case of single hole panel mounting		IP65	
rated operational voltage (AC poles)	Ue		V ac
rated operational current (AC poles)	Ie		A ac
number of AC poles			
auxiliary contact(s), AC15		No auxiliary contact	
auxiliary contact ratings			
weight		384	g
accessories:	-		




Mounting instructions

In the application all ratings have to be respected. When building the switch in an enclosure, the space envelope must be respected according to the applicable standards. The terminals, without interconnection can take copper wires up to 6 mm². The recommended Spade Tongue Terminals may have a maximum width of 9 mm. For CSA and UL applications, registered Spade Tongue Terminals must be used. The registration numbers are UL: E13288 and CSA: LR7189 (for instance type 165015 from Tyco). After mounting, the wiring must be checked and the switch must operate smoothly.

Maintenance

The X type switches are designed for a very long life but it is advised to do some simple yearly maintenance.
- Check the installation for signs of overload or overheating. The terminals may not exceed the limit of 85°C under full load.
- By operating the switch a few times (5x) the contacts will clean themselves and the switch will have a longer life.



Dimensions, specifications and data shown could be subject to change without notice.