

JDA PPC Power plant controller



PPC is a new generation monitoring solution, especially design for solar plant. Monitoring via RS485, one PPC can monitoring up to 32 inverters.

Leading - edge Technology

- ▶ A multi-functional and high-performance communication data logger
一種多功能、高性能的通信數據記錄器
- ▶ Support remote monitoring and maintenance
支持遠程監控和維護
- ▶ Local webserver for easy configuration
本地Web服務器·便於配置
- ▶ Support export limitation with approved meter
通過認可的儀錶支持出口限制

Hardware Parameters

PPC Power plant controller

Power adapter	Input: 100-240V , 50/60Hz AC Output 5V(+/-15%),2A DC
Power consumption	2.5W

Application Parameters

Max. communication range	1000m
Communication with inverters	RS485 (Modbus RTU protocol)
Communication with server	TCP(Modbus TCP protocol)
Support network	WLAN
Data transfer interval	5 Minutes
Default server URL	server.jdauspice.com
Supported servers	Jdauspice Server

General Data

Dimensions(W/H/D)	122/84/25mm
Weight	0.2kg
Language	English
Mounting options	Wall-mount
Ambient temperature range	- 30 °C ~ + 60 °C
Degree of protection	IP30
Warranty	2 years

Certification

CE
