



## DT-102-SS-XXX-AT2 Stainless Steel ATEX Approved iKey Keyboard

### DT-102-SS-XXX-AT2 Main Features

- FM Approval ATEX Zone 2
- Integrated Touchpad
- Stainless steel keys and case
- 10-Key Numeric Pad

### DT-102-SS-XXX-AT2 Typical Applications

- Industrial / Manufacturing Sites
- Mining / Down Hole Environments
- Oil and Gas Environments



### ■ Product Description

iKey manufactures peripherals designed to reduce the risk of failure in hazardous environments. The new DT-102-XXX-AT2, part of the DT-102-EX™ line, carries FM-approval for ATEX Zone 2 area, making it an ideal solution for locations where explosive gases may be present.

Built with an industrial grade stainless steel case and keys, the DT-102-XXX-AT2 is virtually indestructible and tamperproof. Designed as a complete data input solution, it features an integrated touchpad and 10-key numeric pad. It also ships with optional bulkhead cables for complete protection.

NOTE: When ordering please note the cable type in the XXX portion of the part number.



### Technical Specifications

<b>Manufacturer</b>	iKey
<b>Shock</b>	3 x 11 ms pulses of 50g on each of 3 axes
<b>Cable</b>	Where XXX= PS/2, CX, or USB Note: Compatible and certified isolation barriers must be used.
<b>Hazardous Location Ratings</b>	Ex ic IIC T4; Ta=60C IP65
<b>Key Switch</b>	MATERIAL: Brushed Stainless Steel LIFE; Greater than 10 Million Cycles TRAVEL: 0.079 in. (2.01 mm) ACTUATION FORCE: 4.23 oz. +/- 0.18 oz (120 g +/- 5g)
<b>Vibration</b>	POWER SPECTRAL DENSITY: 04g/HZ FREQUENCY OF RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
<b>Power</b>	Reference Drawing Numbers HL-0015 Power Requirements.
<b>Compatability</b>	All Windows Operating Systems
<b>Temperature Range</b>	STORAGE: -40C to +65C (-40F to + 149F) OPERATING: -20C to +60C (-4F to + 140F)
<b>Weight</b>	5.50 lbs +/- 0.10 lbs (2.49 kg +/- 0.5 kg)
<b>Warranty</b>	1 Year Limited Warranty
<b>Humidity</b>	100% Humidity Resistant
<b>Dimensions</b>	15.32" x 7.42" x 1.8" (w-h-d) 38.9mm x 188mm x 46mm
<b>Model Number(s)</b>	DT-102-SS-USB-AT2DT-102-SS.PS2-AT2DT -102-SS.CX-AT2



DT-102-SS BACK / MOUNTING

