



MultiGasScan™ Series

Model MGScan 200

Confined Space Entry Monitor with PID
Simultaneously monitor up to 5 gases



Special Features:

- The first multi-range PID instrument with SMART sensors for oxygen, combustible gases and any two combinations of toxic gases;
- Multi-range PID sensor from ppm to 4,000 ppm;
- Fast response and recovery during measurement;
- PID sensor with built-in humidity and temperature sensors on board for real-time compensation and accurate readings;
- Ex-approved for application in hazardous environment;
- Health and safety mode available as standard;
- Simultaneous display of all readings in large LCD with backlit;
- Automatic and manual data-logging feature as standard;
- Data-download to computer via USB cable;
- Comes with free interactive user-configurable software;
- Library with more than 70+ VOCs and their response factors;
- Upgraded to higher version.



Ultra perfection.

Riding on the achievements from legacy of precision
and inner functionality.

MultiGasScan™ Series

Model MGScan 200

Specification:

		MGScan 225 (OFCH Type)	MGScan 246 (SMART Type)
Sensors	5 x sensors; plug-in type	●	●
Type	Range		
PID (10.6 eV)	0-2000 ppm	●	●
	0-4000 ppm	●	●
	* with Temperature and Humidity compensation on board	●	●
Combustible Gases	0-100%LEL	●	●
	0.0-5.0%Volume	●	●
Oxygen	0-30.0% Volume	●	●
CO (Toxic 1)	0-999 ppm	●	●
H2S (Toxic 2)	0-100 ppm	●	●
	* Toxic Sensor 1 and 2 can be replaced with list of toxic sensors as follows:		
Cl2	0.0-20.0 ppm		
ClO2	0.0-2.0 ppm		
HCN	0-50 ppm		
NH3	0-100 ppm	●	●
NO2	0.0-20.0 ppm		
PH3	0.0-5.0 ppm		
SiH4	0-50 ppm		
	* other toxic sensors to be updated; available on request.		
Response factor	Built-in library for up to 70 gases.	●	●
Datalogging	User downloadable datalogger	●	●
Communication	PC to instrument via USB; GDS-Scan PC software for instrument configuration and data handling	●	●
Upgradeable	Able to upgrade to higher version of MGScan series	●	●

Common specification to all:

Size	L182 mm x W90 mm (tapering to 60 mm) x D52 mm
Weight	approx. 580 g
Measurement	LEL %LEL or %Vol (selectable) VOC ppm or mg/m3 (selectable)
Pump	built-in; Standard tubing length 3 m; Up to 50 m length as user options.
Alarms	audible and visual alarm (95 dB and LEDs) high alarm (adjustable) low alarm (adjustable) STEL and TWA alarms (adjustable) additional diagnostic alarms alarm and display for low battery status low flow alarm vibrator alarm calibration due alarm
Calibration	Automatic 2-point field calibration for zero and span
Auto zero	Yes
Battery	rechargeable Li-ion battery pack drop-in charging cradle
Operation Time	Up to 16 hours continuous operation

Display	Large LCD 23cmx7cm; 128x64 pixels with backlight
Keypad	Three tactile buttons operation
Readout	Instantaneous and simultaneous for 5 gas values TWA and STEL values for VOC, Toxic 1 and 2 High and Low values for all gases Next calibration date Real-time dock Battery status
Tagging	Add, remove and edit tags on measurements
Op. Temperature	-20 deg C to +50 deg C
Op. Humidity	0%RH to 95%RH (non-condensing)
Approval	Ex ib d IIC T4 (pending)
IP rating	IP65
EMI/RFI	Compliance to EN 50270
Communication	PC connectivity via USB and docking station using GDS-Scan PC software

The above specifications are correct as of the time of printing; Informations are subject to changes due to on-going product improvements.



Distributed by: