

GE PLASTICS KOREA LTD

231-8 NONHYUN-DONG, KANGNAM KU, SEOUL KR

923(f1), 943(f1)**Polycarbonate (PC), flame retardant, "Lexan", furnished as pellets**

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
AO	1.5	V-0	3	3	130	120	125
	3.0	V-0	2	2	130	120	130
	6.0	V-0	1	2	130	120	130

Comparative Tracking Index (CTI): **3**Dimensional Stability (%): **0.1**High-Voltage Arc Tracking Rate (HVTR): **3**High Volt, Low Current Arc Resis (D495): **7**Dielectric Strength (kV/mm): **24**Volume Resistivity (10xohm-cm): **15****(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.****NOTE - Material designations may be followed by any combination of numbers or letters.**

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

Report Date: 1990-02-09

Last Revised: 2003-10-24

Underwriters Laboratories Inc®

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness Tested (mm)	Value
IEC Flammability	IEC 60695-11-10	Class (color)	1.5	V-0 (AO)
			3.0	V-0 (AO)
			6.0	V-0 (AO)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m2	-	-
ISO Izod Impact	ISO 180	kJ/m2	-	-
ISO Charpy Impact	ISO 179-2	kJ/m2	-	-

Underwriters Laboratories Inc®