

Single Phase (2 MOV Modules) Surge Protective Devices Type D1-40/***-2MV-R

Surge arrester for low-voltage power supply system protection against surges at the boundaries from lightning protection zone 0B-1 and higher.

- Class II (C) arrester in according with IEC61643-1:2005. ANSI/IEEE C62.41
- Fail Safe System (Patent)
- Two part design consisting of base and plug-in protection module.
- High energy MOV (Metal Oxide Varistor) inside.
- Reliable supervision due to disconnection device.
- Fault indication by red indication flag in window.
- Fast response.
- With remote alarm terminal optional.

Rapid thermal disconnection under TOV ;
Inbuilt Arc - extinguishing device.





Characteristics

Type		D1-40/***-2MV-R									
		75	150	175	275	300	320	385	440	550	600
In accordance with		IEC61643-1:2005 ; UL1449 3rd									
Category IEC/VDE		II / C									
Max. continuous operating voltage		75/100	150/200	175/225	275/300	300/385	320/420	385/505	440/585	550/745	600/800
Nominal discharge current (8/20) In	L-N	20KA									
	N-PE	20KA									
Max. discharge current (8/20) Imax	L-N	40KA									
	N - PE	40KA									
Voltage protection level ≤	@In	0.5KV	0.8KV	0.8KV	1.4KV	1.5KV	1.6KV	1.8KV	2.2KV	2.8KV	3.0KV
	@3KA	0.3KV	0.5KV	0.6KV	1.0KV	1.0KV	1.1KV	1.3KV	1.5KV	2.0KV	2.0KV
Response time	L-N	≤25 ns									
	N-PE	≤25 ns									
Follow current	L-N	No									
	N-PE	No									
Backup fuse (only required if not already provided in mains)		125A gL/gG									
Operating temperature range		- 40°C~ + 80°C									
Cross-section of connection wire		Single-strand 35mm ² ; multi-strand 25mm ²									
Mounting		35mm DIN-rail in accordance with EN 50022/DIN46277-3/DIN43880									
Enclosure material		Thermoplastic ; extinguishing degree UL94 V-0									
Degree of protection		IP20									
Installation width		2 modules , DIN 43880									
Thermal disconnecter		Internal green – normal red - failure									
Remote alarm contact		Optional									
Additional data for Remote Alarm Contacts											
Remote alarm contact type		floating changeover contact									
Switching capability UN/IN		AC: 250V/0.5A DC: 250V/0.1A ; 125V/0.2A ; 75V/0.5A									
Cross_section of connection wire		Max. 1.5mm ²									

Note: Subject to change without any notice.

Dimensions and Diagram



All dimension in mm