

SANTERNO TG100 - TG125 NA

PV inverter for commercial rooftop



Advantages

- 100, 125 kWac output power
- Multiple output voltage range (connection in USA and CANADA)
- 96.5% CEC weighted efficiency
- CSA 107.1-01, UL 1741, IEEE 1547 certified.
- Wake up features for data access at night
- Available outdoor (Nema 3R) or indoor version
- Integrated monitoring and datalogger
- Outstanding grid-power quality



Product features

MPP Tracking	315-600 Vdc	Operating temperature (full power)	-25° C to +45° C for TG 100 -13° F to 113° F
Current THD	<3%		-25° C to +40° C for TG 125 -13° F to 104° F
Degree of protection	Nema 3R outdoor installation	Nominal output frequency	60 Hz
Cooling system	Adjustable forced air		

Technical features	TG 100 NA	TG 125 NA
DC Input Voltage Range	315-600 Vdc	315-600 Vdc
Output power level	100 kWac	125 kWac
Output voltage range	208, 240, 480, 600 Vac	208, 240, 480, 600 Vac
Power Factor	> 0.99	> 0.99
AC output current limit	315, 273, 137, 108 A	347, 301, 151, 121 A
Maximum DC current	363 A	429 A

Efficiency

Peak Efficiency	97%	97%
CEC Wheighted Eff.	96.5%	96.5%

Mechanical Features

Dimensions (WxDxH)	55.1" x 31.5" x 94.5"	55.1" x 31.5" x 94.5"
Weight	3085 lbs	3300 lbs



JD Auspice Co., Ltd
 3F., No.288, Sec. 2, Zhonghua Rd., Xinzhuang
 Dist., New Taipei City 24246, Taiwan R.O.C.
 TEL: 886-2-8991-2796 FAX: 886-2-8991-9298
 service@jdauspice.com www.jdauspice.com