



IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

NMSJ2.E362334

Photovoltaic Manual-disconnect Switches - Component

[Page Bottom](#)

Photovoltaic Manual-disconnect Switches - Component

[See General Information for Photovoltaic Manual-disconnect Switches - Component](#)

SANTON INTERNATIONAL BV

E362334

Hekendorpstraat 69

Po-Box 59024, 3008Pa Rotterdam

3079 DX Rotterdam, THE NETHERLANDS

Industrial control switches, open type, Model(s) XBU, may be followed by E or HP, followed by 0 to 9, followed by 0 to 9, followed by 0 to 9, followed by 0 to 9, may be followed by -001 to -ZZZZZ, followed by /, followed by 0 to 9.

Industrial control switches, open type, panel mounting, Model(s) U40C15B02ACB-CA101

Industrial control switches, open type, panel mounting, Model(s) X, may be followed by 100., may be followed by 10, 12, 16, 25, 30 or 36, followed by B, D, P or R, may be followed by L, may be followed by C, followed by U, may be followed by S, may be followed by 1, 2, 3, 4 or 6, may be followed by C, D, O, R, S or W, may be followed by 2, 3 or 4, may be followed by E, F, G, H, L, M, N, T or U, followed by -, followed by a letter or a letter in brackets, may be followed by 00 to 99, may be followed by E, F, G, H, L, M, N, T, U, V or Z, may be followed by -00 to -60, may be followed by .00 to .25, may be followed by .2 or .3, may be followed by -000001 to ZZZZZ.

Industrial control switches, open type, panel mounting, Model(s) X, may be followed by 60., may be followed by 10, 12, 16, 25 or 30, followed by B, D, P or R, may be followed by L, followed by U, may be followed by S, may be followed by 1, 2, 3, 4, 6 or 8, may be followed by C, D, O, R, S or W, may be followed by 2, 3 or 4, may be followed by E, F, G, H, L, M, N, T or U, followed by -, followed by a letter or a letter in brackets, may be followed by 00 to 99, may be followed by E, F, G, H, L, M, N, T, U, V or Z, may be followed by -00 to -60, may be followed by .00 to .25, may be followed by .2 or .3, may be followed by -000001 to ZZZZZ.


Industrial control switches, open type, panel mounting, Model(s) XA, may be followed by 60., may be followed by 10, 12, 16 or 25, followed by B, D, P or R, may be followed by L, followed by U, may be followed by S, may be followed by 1, 2, 3, 4, 6, 8, 10 or 12, may be followed by C, D, O, R, S or W, may be followed by 2, 3 or 4, may be followed by E, F, G, H, L, M, N, T or U, followed by -, followed by a letter or a letter in brackets, may be followed by 00 to 99, may be followed by E, F, G, H, L, M, N, T, U, V or Z, may be followed by -00 to -60, may be followed by .00 to .25, may be followed by .2 or .3, may be followed by -000001 to ZZZZZ.

Industrial control switches, open type, panel mounting, Model(s) XC, may be followed by 100., may be followed by 20, 30 or 50, followed by B, D, P or R, may be followed by L, may be followed by C, followed by U, may be followed by S, may be followed by 1, 2, 3, 4, 6 or 8, may be followed by C, D, O, R, S or W, may be followed by 2, 3 or 4, may be followed by E, F, G, H, L, M, N, T or U, followed by -, followed by a letter or a letter in brackets, may be followed by 00 to 99, may be followed by E, F, G, H, L, M, N, T, U, V or Z, may be followed by -00 to -60, may be followed by .00 to .25, may be followed by .2 or .3, may be followed by -000001 to ZZZZZ.

Industrial control switches, open type, panel mounting, Model(s) XC, may be followed by 125., may be followed by 21, followed by B, D, P or R, may be followed by L, may be followed by C, followed by U, may be followed by S, may be followed by 1, 2, 3, 4, 6 or 8, may be followed by C, D, O, R, S or W, may be followed by 2, 3 or 4, may be followed by E, F, G, H, L, M, N, T or U, followed by -, followed by a letter or a letter in brackets, may be followed by 00 to 99, may be followed by E, F, G, H, L, M, N, T, U, V or Z, may be followed by -00 to -60, may be followed by .00 to .25, may be followed by .2 or .3, may be followed by -000001 to ZZZZZ.

Industrial control switches, open type, panel mounting, Model(s) XC, may be followed by 150., may be followed by 13, followed by B, D, P or R, may be followed by L, may be followed by C, followed by U, may be followed by S, may be followed by 1, 2, 3, 4, 6 or 8, may be followed by C, D, O, R, S or W, may be followed by 2, 3 or 4, may be followed by E, F, G, H, L, M, N, T or U, followed by -, followed by a letter or a letter in brackets, may be followed by 00 to 99, may be followed by E, F, G, H, L, M, N, T, U, V or Z, may be followed by -00 to -60, may be followed by .00 to .25, may be followed by .2 or .3, may be followed by -000001 to ZZZZZ.

Industrial control switches, open type, panel mounting, Model(s) XC, may be followed by 75., may be followed by 40 or 50, followed by B, D, P or R, may be followed by L, may be followed by C, followed by U, may be followed by S, may be followed by 1, 2, 3, 4, 6 or 8, may be followed by C, D, O, R, S or W, may be followed by 2, 3 or 4, may be followed by E, F, G, H, L, M, N, T or U, followed by -, followed by a letter or a letter in brackets, may be followed by 00 to 99, may be followed by E, F, G, H, L, M, N, T, U, V or Z, may be followed by -00 to -60, may be followed by .00 to .25, may be followed by .2 or .3, may be followed by -000001 to ZZZZZ.

Marking: Company name, model designation and the Recognized Component Mark, .

[Last Updated](#) on 2018-02-26

[Questions?](#)
[Print this page](#)
[Terms of Use](#)
[Page Top](#)

◆ 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission

from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".